

FX2NC-32BL Battery MODEL CODE: 09M129

STARTUP AND MAINTENANCE PRECAUTIONS **MARNING**

- Les the battery for memory backup correctly in conformance to the manual of each product.

 Use the battery only for the specified purpose.

 Connect the battery correctly.

 Do not charge, disassemble, heat, put in fire, short-circuit, connect reversely, weld, swallow or burn up the battery, or apply excessive forces (vibration, impact, drop, etc.) on the battery.

 Do not store or use the battery in a place at high temperature or exposed to direct sunlight.

 Do not expose to water, bring near fire or touch the contents such as liquit leakage directly.

 Incorrect handling of the battery may cause heat excessive generation, burst, ignition, liquid leakage or deformation, and lead to injury, fire or failures and maffunctions of facilities and other equipment. burst, ignition, liquid leakage or deformation, and lead to injury, fire of failures and malfunctions of facilities and other equipment. Power off the Devices with Bulli-in Batteries (all phase) before attaining detaching the battery. Failure to do so may cause electric shock or damage to the product.
 - Please contact a certified electronic waste disposal company for the environmentally safe recycling and disposal of your device.

Applicable model Product name

FX2NC-32BL	FX2NC, FX2N-20GM, F930GOT, F940GOT-H/-RH						
2. Battery Replacement							

Applicable model

For the replacement procedure, refer to the User's Manual of the respective Devices with Built-in Batteries.







Made in Japan MITSUBISHI ELECTRIC CORPORATION

原产地 日本国 合格证

- Battery life: Approx. 3 years (ambient temperature: 25°C) Replacement period: Within 2 or 3 years (Due to natural discharge within all batteries, please prepare a replacement before the above-stated replacement period.) For details, refer to the User's Manual of the respective Devices with Built-in Batteries.

Precautions for Battery Transportation hen transporting lithium batteries, follow the When follow the transportation regulations.

Product Lithium Content Product name Mass Battery type supply status (gram/unit) (gram/unit)

FX2NC-32BL	lithium metal battery	Cell	0.15	30					
*1 The value indicates the mass with packaging.									
The value malected the made with packaging.									
Comply with IATA Dangerous Goods Regulations, IMDG code and									
the local transport regulations when transporting products listed									
the road transport regulations when transporting products noted									

Also, consult with the shipping carrier.

5. Handling of Batteries in EU Member States *1 This symbol to the left is for EU member states for battery EU

This symbol to the lock of St. 2 - only.

The symbol is specified in the new EU Battery Directive (2006/66/EC) Article 20 "Information for end-users" and Annex II.



- The symbol to the above indicates that batteries need to be disposed of separately from other wastes.

 The new EU Battery Directive (2006/66/EC) requires the following when marketing or exporting batteries and/or devices with built-in batteries to EU member states. To print the symbol on batteries, devices, or their
- packaging To explain the symbol in the manuals of the products
 - Battery type

FX2NC-32BL	Lithium Thionyl Chloride Battery				

(15) Note: This symbol mark is for China only.

「电器电子产品有害物质限制使用标识要求」的表示方式

含有有害6物质的名称,含有量,含有部品 本产品中所含有的有害6物质的名称,含

含有量, 含有部品如 下表所示。 产品中有害物质的名称及含量

左宝物氏

部件名称		1月 17 70 70								
		铅 (Pb)	汞 (Hg)	镉 (Cd)	六价铬 (Cr(VI))	多溴联苯 (PBB)	多溴 二苯醚 (PBDE)			
可编程	外壳	0	0	0	0	0	0			
控制器	印刷基板	X	0	0	0	0	0			
本表格依据SJ/T 11364的规定编制。										

- 〇:表示该有害物质在该部件所有均质材料中的含量均在GB/T
- 26572规定的限量要求以下。 ※:表示该有害物质至少在该部件的某一均质材料中的含量超出 GB/T 26572规定的限量要求。
- 基于中国标准法的参考规格: GB/T15969.2