

Programmable Controller MELSEC iO-F



R



MFLSEC iQ-F FX5-422-BD-GOT

Hardware Manual



Manual Number	JY997D60101
Revision	Н
Date	April 2022

This manual describes the part names dimensions installation and specifications of the product. Before use, read this manual and manuals of relevant products fully to acquire proficiency in handling and operating the product. Make sure to learn all the product information, safety information, and

And, store this manual in a safe place so that you can take it out and read it whenever necessary. Always forward it to the end user. Registration

The company names, system names and product names mentioned in this manual are either registered trademarks or trademarks of their respective companies. In some cases, trademark symbols such as 'TM' or '®' are not specified in this manual

Effective April 2022

Specifications are subject to change without notice.

Safety Precautions (Read these precautions before use.)

This manual classifies the safety precautions into two categories:

MARNING and **MCAUTION**

<u></u> MARNING	Indicates that incorrect handling may cause hazardous conditions, resulting in death or severe injury.
∴CAUTION	Indicates that incorrect handling may cause hazardous conditions, resulting in minor or moderate injury or property damage.

Depending on the circumstances, procedures indicated by ACAUTION may also cause severe injury.

It is important to follow all precautions for personal safety

Associated Manuals

Manual name	Manual No.	Description
MELSEC iQ-F FX5S/ FX5UJ/FX5U/FX5UC User's Manual (Hardware)		Describes the details of hardware of the CPU module, including performance specifications, wiring, installation, and maintenance.

How to obtain manuals

For the necessary product manuals or documents, consult with your local Mitsubishi Electric representative

Applicable standards

FX5-422-BD-GOT complies with the EC Directive (EMC Directive) and UKCA marking. Further information can be found in the following manual.

→ MELSEC iQ-F FX5S/FX5UJ/FX5U/FX5UC User's Manual (Hardware) Regarding the standards that relate to the CPU module, please refer to either the product catalog or consult with your nearest Mitsubishi product provider.

Attention

This product is designed for use in industrial applications.

1 Outline


RS-422 expansion board FX5-422-BD-GOT connects to GOT using MINI-DIN 8-pin connectors and performs RS-422 communication.

1.1 Incorporated Items

Check that the following product and items are included in the package:

Product	FX5-422-BD-GOT communication board
Included items	M3×8 tapping screws for installation: 2 pcs. Hardware Manual (This manual)

1.2 External Dimensions and Part Names



MASS (Weight): Approx 20 g Outer painting color: Munsell N1.5

- [1] RS-422 connector (8-pin MINI-DIN, female)
- [2] Mounting holes (2-63.2)
- [3] Connector cover
- [4] RD LED (green) Lighting while receiving data
- [5] SD LED (green) Lighting while sending data
- [6] CPU module connector

2. Installation

INSTALLATION PRECAUTIONS

⚠ WARNING

- Make sure to cut off all phases of the power supply externally before attempting installation or wiring work. Failure to do so may cause electric shock or damage to the product.
- Use the product within the generic environment specifications described in the User's Manual (Hardware) of the CPU module used. Never use the product in areas with excessive dust, oily smoke, conductive dusts corrosive gas (salt air, Cl2, H2S, SQ2 or NQ2), flammable gas, vibration of impacts, or expose it to high temperature, condensation, or rain and wind. If the product is used in such conditions, electric shock, fire, malfunctions

INSTALLATION **⚠** CAUTION PRECAUTIONS

deterioration or damage may occur.

- Do not touch the conductive parts of the product directly. Doing so may cause device failures or malfunctions
- When drilling screw holes or wiring, make sure that cutting and wiring debris do not enter the ventilation slits of the PLC. Failure to do so may cause fire, equipment failures or malfunctions.
- Connect the expansion board and expansion adapter securely to their designated
- Loose connections may cause malfunctions.
- Make sure to affix the expansion board with tapping screws Tightening torque should follow the specifications in the manual If the screws are tightened outside of the specified torque range, poor connections may cause malfunctions.
- Work carefully when using a screwdriver such as installation of the product. Failure to do so may cause damage to the product or accidents.

For the installation, refer to the following manual

→ MELSEC iQ-F FX5S/FX5UJ/FX5U/FX5UC User's Manual (Hardware)

3. Specifications

STARTUR AND MAINTENANCE DDECALITIONS

CAUTION

- Do not disassemble or modify the PLC.
- Doing so may cause fire, equipment failures, or malfunctions. For repair, contact your local Mitsubishi Electric representative.
- Do not drop the product or exert strong impact to it.
- Doing so may cause damage

DISBOSAL PRECAUTIONS

CAUTION

Please contact a certified electronic waste disposal company for the environmentally safe recycling and disposal of your device

TRANSPORTATION PRECAUTIONS

↑ CAUTION

The product is a precision instrument, During transportation, avoid impacts larger than those specified in the general specifications by using dedicated packaging boxes and shock-absorbing palettes.

Failure to do so may cause failures in the product. After transportation, verify operation of the product and check for damage of the mounting part, etc.

3.1 Applicable CPU module

Model name	Applicability
FX5S CPU module	From first production
FX5UJ CPU module	From first production
FX5U CPU module	From first production

3.2 General Specifications

The general specifications are equivalent to the CPU module. For general specifications, refer to the following manual.

However since the product is not isolated between communication lines and the CPLI module, please do not perform any dielectric withstand voltage tests or insulation resistance tests to this product.

→ MELSEC iQ-F FX5S/FX5UJ/FX5U/FX5UC User's Manual (Hardware)

3.3 Power Supply Specification

Item	Specification
Rated voltage	5 V DC
Current consumption	20 mA*1/5 V DC

*1 When the GOT 5 V type is connected with this product, the current consumption increases. For the current consumption, refer to the manual of the model to be

3.4 Performance specifications

Item	Specification
Transmission standard	Conforming to RS-422
Maximum transmission distance*1	According to the specification of the GOT
Connection method	8-pin MINI-DIN, female
Insulation	Not insulated (Between communication line and CPU module)
Communication method	Half-duplex
Baud rate	9600/19200/38400/57600/115200 (bps)

*1 For the maximum transmission distance, refer to the manual of the model to be

This manual confers no industrial property rights or any rights of any other kind. nor does it confer any patent licenses. Mitsubishi Electric Corporation cannot be held responsible for any problems involving industrial property rights which may occur as a result of using the contents noted in this manual.

Exclusion of loss in opportunity and secondary loss from warranty liability Regardless of the gratis warranty term, Mitsubishi shall not be liable for compensation to:

- (1) Damages caused by any cause found not to be the responsibility of Mitsubishi.
- (2) Loss in opportunity, lost profits incurred to the user by Failures of Mitsubishi products.
- (3) Special damages and secondary damages whether foreseeable or not, compensation for accidents, and compensation for damages to products other than Mitsubishi products.
- (4) Replacement by the user, maintenance of on-site equipment, start-up test run and other tasks

- This product has been manufactured as a general-purpose part for general industries, and has not been designed or manufactured to be incorporated in a device or system used in purposes related to human life
- Before using the product for special purposes such as nuclear power, electric power, aerospace, medicine or passenger movement vehicles, consult with Mitsubishi Electric.
- This product has been manufactured under strict quality control. However when installing the product where major accidents or losses could occur if the product fails install appropriate backup or failsafe functions in the system

MITSUBISHI ELECTRIC CORPORATION