



## **TECHNICAL BULLETIN**

**[ 1 / 5 ]**

[Issue No.] GOT-A-0198-Q

[Title] Precautions for Transport Recommendations on Lithium Batteries for Overseas

[Date of Issue] January 2023 (Ver. Q: July 2025)

[Relevant Models] GOT3000 Series, GOT2000 Series, GOT1000 Series, and GOT SIMPLE Series

---

Thank you for your continued support of Mitsubishi Electric Graphic Operation Terminal (GOT).

This technical bulletin summarizes the handling procedure for lithium batteries under air transport regulations (hereinafter referred to as the UN Recommendations), based on the IATA Dangerous Good Regulations.

The IATA Dangerous Goods Regulations are revised annually, with changes to their requirements.

If you transport lithium batteries, you are responsible for the shipment. Therefore, be sure to check the latest editions of the IATA Dangerous Goods Regulations and the UN Recommendations.

Under the UN Recommendations, batteries are classified as hazardous (Class 9) or non-hazardous based on their lithium content, and the handling methods differ accordingly.

### **Contents**

1. Models subject to the UN Recommendations .....	2
2. Effective dates of the UN Recommendations .....	3
3. Transport guidelines for models subject to the UN Recommendations .....	3
3.1 Transport of lithium batteries packed by themselves .....	3
3.2 Transport of lithium batteries contained in or packed with equipment .....	3
REVISIONS .....	5

[Issue No.] GOT-A-0198-Q

## 1. Models subject to the UN Recommendations

The following shows the GOT2000/1000 series products that are subject to the UN Recommendations. For the transport guidelines, refer to Chapter 3.

The battery for the GOT3000 series is sold separately.

For compatible batteries, refer to the instruction manual for each product.

Table 1-1 Products subject to the UN Recommendations (Lithium batteries packed by themselves)

Product	Model	Lithium content	Battery weight	Type	Transport classification
Battery	GT11-50BAT	0.15 g	7.2 g	Lithium metal battery (cell)	Non-dangerous goods
	GT15-BAT	0.57 g *2	17 g *2		Dangerous goods *1

\*1 Batteries or cells with a lithium content of more than 0.3 g are classified as dangerous goods (Class 9) according to packing instructions.

\*2 From the August 2017 production, the lithium content will be 0.57 g and the battery weight will be 17 g.

For the details, refer to the following.

→ Changes to the GOT1000 Series Battery GT15-BAT (GOT-A-0118)

Table 1-2 Products subject to the UN Recommendations (Lithium batteries contained in equipment)

Series	Model	Model	Type	Transport classification
GOT2000 *1	GT2715-XTBA, GT2715-XTBD, GT2712-STBA, GT2712-STWA, GT2712-STBD, GT2712-STWD, GT2710-STBA, GT2710-STBD, GT2710-VTBA, GT2710-VTWA, GT2710-VTBD, GT2710-VTWD, GT2708-STBA, GT2708-STBD, GT2708-VTBA, GT2708-VTBD, GT2705-VTBD, GT2512-STBA, GT2512-STBD, GT2512F-STNA, GT2512F-STND, GT2510-VTBA, GT2510-VTBD, GT2510-VTWA, GT2510-VTWD, GT2510F-VTNA, GT2510F-VTND, GT2508-VTBA, GT2508-VTBD, GT2508-VTWA, GT2508-VTWD, GT2508F-VTNA, GT2508F-VTND, GT2505-VTBD, GT2512-WXTBD, GT2512-WXTSD, GT2510-WXTBD, GT2510-WXTSD, GT2507-WTBD, GT2507-WTSD, GT2507T-WTSD, GT2505HS-VTBD, GT2107-WTBD, GT2107-WTSD, GT2105-QTBD, GT2105-QMBDS, GT2104-RTBD, GT2104-PMBD, GT2104-PMBDS, GT2104-PMBDS2, GT2104-PMBLS	GT11-50BAT (1 pc)	Lithium batteries contained in equipment	Non-dangerous goods
	GT2506HS-VTBD	GT15-BAT (1 pc)		
GOT1000	GT1695M-XTBA, GT1695M-XTBD, GT1685M-STBA, GT1685M-STBD, GT1675M-STBA, GT1675M-STBD, GT1675M-VTBA, GT1675M-VTBD, GT1675-VNBA, GT1675-VNBD, GT1672-VNBA, GT1672-VNBD, GT1665M-STBA, GT1665M-STBD, GT1665M-VTBA, GT1665M-VTBD, GT1662-VNBA, GT1662-VNBD, GT1665HS-VTBD	GT15-BAT (1 pc)		
	GT1655-VTBD, GT1455-QTBD, GT1455-QTBDE, GT1450-QLBD, GT1450-QLBDE, GT1450-QMBD, GT1450-QMBDE, GT1455HS-QTBDE, GT1450HS-QMBDE, GT1155-QTBD, GT1155-QTBDQ, GT1155-QTBDA, GT1155-QSBD, GT1155-QSBDQ, GT1155-QSBDA, GT1150-QLBD, GT1150-QSBDQ, GT1150-QLBDA, GT1155HS-QSBD, GT1150HS-QLBD, GT1055-QSBD, GT1050-QBBD, GT1045-QSBD, GT1040-QBBD, GT1030-LBD, GT1030-LBD2, GT1030-LBDW, GT1030-LBDW2, GT1030-LBL, GT1030-LBLW, GT1030-LWD, GT1030-LWD2, GT1030-LWDW, GT1030-LWDW2, GT1030-LWL, GT1030-LWLW, GT1030-HBD, GT1030-HBD2, GT1030-HBDW, GT1030-HBDW2, GT1030-HWD, GT1030-HWD2, GT1030-HWDW, GT1030-HWDW2, GT1030-HBL, GT1030-HBLW, GT1030-HWL, GT1030-HWLW	GT11-50BAT (1 pc)		
GOT SIMPLE	GS2512-WXTBD	GT11-50BAT (1 pc)		

\*1 The models of the CC-Link IE Field Network communication unit set are also subject to the UN Recommendations.

For the models of the CC-Link IE Field Network communication unit set, refer to the following.

→ GOT2000 series catalog (L(NA)08274ENG)

**2. Effective dates of the UN Recommendations**

Table 2-1 shows the dates when the UN Recommendations are taken effect in each transport.

Table 2-1 Enforcement status of the UN Recommendations

Transport	UN Recommendations	Enforcement status
Air transport (ICAO *1/IATA *2)	Controlled	Enforced
Sea transport (IMDG Code *3)	Controlled	Enforced
Land transport (domestic)	Not controlled	Not determined
Land transport (international)	Depends on regulations of each country.	Depends on regulations of each country. United States: Enforced Europe: Enforced

\*1 ICAO: International Civil Aviation Organization

\*2 IATA: International Air Transport Association

\*3 IMDG Code: International Maritime Dangerous Goods Code specified by IMO (International Maritime Organization)

**3. Transport guidelines for models subject to the UN Recommendations**

When transporting the GOT products, note the following points.

**3.1 Transport of lithium batteries packed by themselves****(1) GT11-50BAT**

Packaging	Classification	Requirements	Reference
The net weight of batteries is 2.5 kg or less in one package.	UN3090 PI968 Section II	<ul style="list-style-type: none"> <li>Capable of withstanding a 1.2 m drop test</li> <li>Bearing the lithium battery handling label (Dimensions: 120 x 110 mm)</li> </ul>	Figure 1 in Section 3.2

**(2) GT15-BAT**

Packaging	Classification	Requirements	Reference
The number of batteries is 8 or less in one package.	UN3090 PI968 Section II	<ul style="list-style-type: none"> <li>Capable of withstanding a 1.2 m drop test</li> <li>Bearing the lithium battery handling label (Dimensions: 120 x 110 mm)</li> </ul>	Figure 1 in Section 3.2
The number of batteries is 9 or more in one package.	UN3090 PI968 Section IB	<ul style="list-style-type: none"> <li>Capable of withstanding a 1.2 m drop test</li> <li>Bearing the lithium battery handling label (Dimensions: 120 x 110 mm)</li> <li>Handled as dangerous goods (Class 9), such as bearing the Class 9 hazard label</li> </ul>	Figure 1 in Section 3.2 Figure 2 in Section 3.2

As of January 1, 2015, lithium metal batteries packed by themselves are forbidden for transport as cargo on passenger aircraft.

However, such lithium metal batteries can still be transported by vessel or cargo aircraft after January 1, 2015.

**3.2 Transport of lithium batteries contained in or packed with equipment****(1) Lithium batteries contained in equipment (UN3091) must be transported in accordance with Section II of Packing Instruction 970.**

However, no special handling is required in the following cases:

- The number of batteries is 4 or less in one package.
- The net weight of batteries is 5 kg or less in one package.

**(2) Lithium batteries packed with equipment (UN3091) must be transported in accordance with Section II of Packing Instruction 969.**

Lithium batteries packed with or contained in equipment can be transported by passenger aircraft.

**PRECAUTIONS**

- The overpack must also bear the lithium battery handling label (Figure 1).
- The above requirements and actions are specified by Mitsubishi Electric, and they may differ depending on the carrier. For details, contact the carrier.
- All lithium batteries are required to have passed the United Nations safety tests.  
All the batteries used in our GOT products shown below have passed the battery safety tests, and no action needs to be taken by the customers.

## → 1. Models subject to the UN Recommendations

When transporting a lithium battery, obtain the document on which you can refer to the summary of the UN recommended tests (Test Summary) from our company.

(Required from January 1, 2020)



\*: Represents the UN number.

\*\*: Represents the phone number for obtaining more information.

Figure 1 Example of the lithium battery handling label



Figure 2 Example of the Class 9 label

**REVISIONS**

Version	Print Date	Revision
P	January 2023	- First edition
Q	July 2025	- Added the GOT3000 series to the relevant models. - Revised the description to request a check of the latest edition of the IATA Dangerous Goods Regulations.